

## Square Bore Bearing, Tri-Ply Seals, Re-lubricatable

Bearing No.	Type	Dimensions(in) (mm)						Load Cr.	Rating	
		H	di	D	Be	Bi	h			
GW208PP B6	2	1.024	1.102	3.150	0.827	1.438	0.248	22.71	14	
		26.00	28.00	80.00	21.00	36.53	6.30			
GW208PP B5	2	1.180	1.260	3.150	0.827	1.438	0.248	22.71	14	
		29.97	32.00	80.00	21.00	36.53	6.30			
GW208PP B8	2	1.180	1.260	3.150	1.188	1.438	0.248	22.71	14	
		29.97	32.00	80.00	30.18	36.53	6.30			
GW209PP B17	2	1.180	1.260	3.375	1.188	1.438	0.248	22.71	14	
		29.97	32.00	85.73	30.18	36.53	6.30			
GW209PP B5	2	1.299	1.378	3.346	1.188	1.438	0.260	24.36	11	
		33.00	35.00	85.00	30.18	36.53	6.60			
GW2090P PB8	2	1.299	1.378	3.346	0.866	1.438	0.260	24.36	11	
		33.00	35.00	85.00	22.00	36.53	6.60			
GW210PP B4	1	1.180	1.260	3.543	1.188	1.188	0.260	27.50	20	
		29.97	32.00	90.00	30.18	30.18	6.60			
GW211PP B4	1	1.180	1.260	3.543	1.188	1.188	0.260	27.50	20	
		29.97	32.000	90.00	30.18	30.18	6.60			
GW211PP B3	1	1.531	1.653	3.938	1.313	1.313	0.302	27.50	20	
		38.89	42.00	100.00	33.34	33.34	7.67			
GW211PP 3	4	1.531	1.653	3.938	1.313	1.313	0.302	33.40	24	
		38.89	42.00	100.00	33.34	33.34	7.67			
GW211PP 17	3	1.531	1.653	3.938	1.313	1.750	0.302	33.40	24	
		38.89	42.00	100.00	33.34	44.45	7.67			
GW214PP B4	1	2.055	2.161	4.921	1.563	1.563	0.354	46.79	31	
		52.20	54.90	125.00	39.69	39.69	9.00			
GW216PP 2	3							71.50	54	
		58.20	59.00	140.00	30.00	63.50	8.90			
DC212TT R	3							47.70	30	
		45.50	48.00	110.00	38.25	50.80	7.60			
		H = SQUARE DIMENSION; di – RELIEF DIAMETER								